

AHT-140UTC7



Specifications :

LCD	
Display Size	7" LCD Monitor
Resolution	1440(RGB)x234(H)
Brightness	350 cd/m ²
Back Light	CCFL
Viewing Area	154.08mm(W)x86.58mm(H)
Video Input	AV input
DVR	
Video Compression	MJPEG
Video Input	BNCx4
Video Output	Video out x2
Display Division	Single/Sequence/Split(1/4)
PTZ control	Support PTZ by using mouse through RS485
System	
IR controller	Yes(Optional)
Mouse	Yes(Combo USB & PS/2 protocol)
Speakers	1.5W x 2
Power Supply	DC12V/ 4A
Dimension (WxHxD)	196x146x180mm
Weight	3.5Kg
Audio	
Audio Input/Output	1/1
Recording	

Recording Resolution	704x288/352x288
Recording Frame Rate	100fps
Recording Mode	Schedule/Event/Motion Detection
Recording Quality	Highest/High/Normal/Low/Lowest
Search & Playback	
Search Mode	Time/Event/Preview
Alarm	
Alarm In/Out	4/1
Storage / Backup	
HDD Storage	Support internal IDE Hard Disk x1; Optional SATA Hard Disk (Factory pre-installation recommended)
Backup Device	USB stick
Connector	
USB	USB 2.0 x1
Mouse	Mouse Port x1
RS485	1



That a player software provided.



PIP function to display the primary video for live surveillance and one auxiliary video for playback in inset window at the same time.

USB Backup



The USB connector on the rear panel of DVR is only for backup and firmware update.



Multiple operation control: Mouse / IR controller (Optional)